



ForkGuard Kerb Barrier

Designed to provide ground level protection for walls, buildings and equipment.




The ForkGuard deflects vehicle forks in shallow angle or low-force impacts. It also acts as a pallet stop or buffer preventing stored goods encroaching into pedestrian areas or walkways.



Floor mounted and bolted from above, the ForkGuard integrates with A-SAFE barriers when installed together.



Technical Information



Material Properties	MEMAPLEX™
Temperature Range	-10°C to 50°C
Ignition Temperature	370°C to 390°C
Flash Point	350°C to 370°C
Toxicity	Not Hazardous
Chemical Resistance	Excellent - ISO/TR 10358
Weathering Stability (Grey Scale)	5/5*
Light Stability (Blue Wool Scale)	7/8**
Static Rating (Surface Resistivity)	1015 - 1016 Ω

* Weathering scale 1 is very poor and 5 is excellent
** Light stability scale 1 is very poor and 8 is excellent

Colour Combinations

Standard Black with Yellow Stripes RAL 9005* PANTONE Black	Standard Black with Grey Stripes RAL 9005* PANTONE Black
---	---

*Please note that the RAL and PANTONE colours listed are the closest match to standard A-SAFE colours, but may not be exact matches of the actual product colour and should be used for guidance only.

